



PRODUCT DETAILS



Dimensions



Accessories



PRETTUS II S

**PRETTUS II S POLISHED REF +
TRANSPARENT COVER LED 1650lm/830
1x15W, DALI, RAL 9003**

DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + transparent cover (PRT)
BEAM ANGLE	65°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear DALI (EDA)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: anodised aluminium Trim: die cast aluminium Cover: PMMA
SURFACE FINISH	Trim: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	0,90
NET LUMEN OUTPUT (Ta=25°C)	1650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	15 W
SYSTEM EFFICACY	110 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	>80 Ra >90 Ra - on request
COLOUR TOLERANCE	3 SDCM
PROTECTION CLASS	I
SERVICE LIFETIME (Ta=25°C)	100,000 hours / L90 / B20
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP54
DIMENSIONS	Diameter - 166 mm, height - 113 mm
OPENING	Diameter - 154 mm
WEIGHT	0,8 kg

AREAS OF APPLICATION EDUCATION

HOSPITALITY

HOUSE AND FLAT

LIDC



HEALTH AND CARE

RETAIL AND PRESENTATION

OFFICE



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.